

Fume Extraction Units



CarryVac 2 Portable Smoke Extractor

The CarryVac 2 P150/P150 AST are two small, lightweight, portable extraction units designed to be carried to the working area. Connected to a welding torch or to an extraction nozzle, the CarryVac 2 units extract the fume directly at source. The polluted air is filtered and captured in a hygienically-packed filter. The CarryVac 2 is equipped with a filter indicator, which shows when the filter must be replaced. It is ideal for maintenance welding, low and medium-duty cycle. The filter capacity is approximately 200kg of solid wire or twelve 15kg spools. The CarryVac 2 P150 AST is equipped with an automatic start/stop function, which increases the service life of each filter and of the unit itself. Please also see ESAB Centrovac extraction torch range.

Delivery contents:

Supplied complete with 2.5m suction hose (Filter Included).

CarryVac 2 P150 220-240V	0700 003 883
CarryVac 2 P150 AST 220-240V	0700 003 884
CarryVac 2 110V	0700 003 885
CarryVac 2 AST 110V	0700 003 886
Hose 45mm, 1.6m	0154 352 015
Hose 45mm, 5m	0700 003 224
Hose 45mm, 15m	0700 003 225
Suction nozzle TM-80, round 80mm	0700 003 221
Suction nozzle TM-200, 200mm wide	0700 003 222
Suction nozzle PM-300, 300mm wide	0700 003 223
Magnet for suction nozzle	0332 010 880
Main filter CarryVac 2	0700 003 004
Pre filter	0468 455 002
Main filter CarryVac (previous model)	0468 455 001

Technical data

Length.....	810mm
Width	226mm
Height	410mm
Weight incl. filter.....	16kg
Mains power supply	230/1~
Output.....	1000 W
Noise level.....	75 dB (A)
Max vacuum	2170mm wp
Filter area	5.3m ²
Air flow (with 2.5m suction hose).....	150m ³ /h
Suction hose diameter	Ø45mm
Filter efficiency.....	99.7%