ABRACS
abrasives and accessories

Phoenix Flat Stone Cutting Disc
115mm x 3.0mm x 22mm

Phoenix discs are produced to O.S.A. Safety standards. Manufactured using premium quality materials, Phoenix II discs offer ultimate performance, long life, outstanding value and one of the best cost per-cut ratio's in the market.



Features & Benefits

- 13,300 Maximum RPM
- Produced to OSA safety standards
- Suitable for use on Natural Stone, Concrete, Bricks, Roof Tiles
- Exceptional cost per cut ratio

Product Specification

Product	115mm x 3.0mm x 22mm Phoenix Flat Stone Cutting Disc
Brand	Phoenix
Code	PH11530FS
Form	CUT-OFF WHEEL
Type	F41
Dimensions	115mm x 3.0mm x 22mm
Grade	C30SBF
Operating Speed	13,300rpm - 80 M/S
Reinforcement	2A
Barcode No.	5060344814423
Commodity Code	68042218

Product Characteristics

Characteristics	Value	Tolerance	Control Method
Thickness	3.0mm	+/- 0.2mm	Internal Method
Weight	58g	+/- 5g	Internal Method
Factor	1.0	+/- 0.2	Internal Method
Deconstruction Speed	Min 23,000rpm	/	EN 12413
Unbalance	Max 1.4g	/	ISO 6103
Run Out Tolerance	0.6mm	/	ISO 13942